



“The HKD Phazer is designed to operate in tight spaces that require narrow, directional throw.”



PHAZER PRODUCT SPECIFICATIONS	
Length (ft / m)	2, 10, 20, 30ft / 3.1, 6.1, 9.1 m
Weight (lbs / Kg) (wo/bracket)	50, 80, 120 lbs / 22.6, 36.2, 54.4 kgs
Wet Bulb Start-Up (Deg. F / C)	28 F / -2.2 C
Water Flow (gpm / lpm)	12 - 50 gpm / 46 - 190 lpm
Minimum Water Pressure (psi / bar)	200 psi / 13.6 bar
Air Flow (cfm / 1m ³ /hr)	5 - 35 cfm / 8.5 - 59 m ³ /hr
Minimum Air Pressure (psi / bar)	85 psi / 5.8 bar
Throw (ft / m)	30 - 125 ft / 9.2 - 38.5 m
Water Flow Stages	5 Stage

Air and water flows represent a range based on the user's desired snowmaking objective.

Add-Ons



KLIK Manual Hydrant



KLIK Auto Hydrant



Traditional Hydrants



HKD Hoses



Portable Sleds

The HKD Phazer is designed to operate in tight spaces that require narrow, directional throw such as cat tracks, lift terminals, and nordic trails. Like the Impulse, the Phazer uses hybrid nucleation and variable air flow so high temperature performance and low temperature production go hand in hand. The Phazer uses the R5 valve to deliver five stages of water flow. Stages one through three increase water flow, while stages four and five further increase water flow while decreasing the air flow. The Phazer can be tower mounted or operated on our Viper Sled or Tripod.