







SV10 PRODUCT SPECIFICATIONS	
Height (ft / m)	10, 20, 30ft / 3.1, 6.1, 9.1 m
Weight (lbs / Kg) (wo/bracket)	50, 80, 120 lbs / 22.6, 36.2, 54.4 kgs
Wet Bulb Start-Up (Deg. F / C)	28 F / -2.2 C
Water Flow (gpm / lpm)	16 - 80 gpm / 61 - 303 lpm
Minimum Water Pressure (psi / bar)	200 psi / 13.6 bar
Air Flow (cfm / 1m³/hr)	5-100 cfm / 8.5 m³/hr - 170 m³/hr
Minimum Air Pressure (psi / bar)	85 psi / 5.8 bar
Throw (ft / m)	30 - 125 ft / 9.2 - 38.5 m
Water Flow Stages	4 Stage

Air and water flows represent a range based on the user's desired snowmaking objective.

Add-Ons



KLIK Manual Hydrant







al H





S-Valve Technology

The HKD SV10 is the simple and bulletproof low energy workhorse in our tower gun lineup. The SV10 is capable of four water flows and uses internal mix nucleators that can be customized to meet the needs of your climate and snowmaking objectives. The SV10 incorporates our S-valve technology, allowing the SV10 to perform optimally in the widest range of temperatures. The SV10 is the godfather of low energy snowmaking towers.